

PRODUCT-DETAILS

E232E-230N

E232E-230N Staircase Switch



Algemene informatie

Type	E232E-230N
Artikelnummer	2CDE110003R0511
EAN	4016779654166
Omschrijving	E232E-230N Staircase Switch

Omschrijving

Staircase time switches with off-delay are operated by push-buttons, which are often equipped with a glow lamp. The switch levers are designed for a glow lamp current of up to 150 mA and are therefore excellently suited for installations in multistorey buildings. The E 232E-230 staircase lighting timer with off-delay has an electromechanical timer relay with synchronous motor drive, which ensures a high level of operational safety in any installation position. The time range can be set in 15-second increments from one to seven minutes. Can be reswitched after 30s. The multifunctional units of the E 232E-230 Multi 10 and E 232E-8/230 Multi 10 product series have 10 functions that can be set on the front of the unit.

Technical

Functie	Electronic
Resetfunctie	Push Button
Toegekende spanning (U_r)	240 V AC
Voedingsspanning	0.85 ... 1.1 V
Maximale besturingsstroom DC	26 mA
Toegekende frequentie (f)	50 ... 60 Hz

Max. gloeilampbelasting	LED Power > 2W 180 W LED Power < 2W 20 W
Vermogensverlies	6 V·A
Lampvermogen	Filament Lamp 2300 W Fluorescent Lamp Compensated 2300 V·A Fluorescent Lamp Shunt Capacitive 1300 V·A Fluorescent Lamp Inductive 2300 V·A Halogen Lamp 2300 W
Minimale schakeltijd	0.02/0.05 seconde
Tijdbereik	0.5 – 20 min. stepless
Voorschakelapparaat	Electronic
Belastingwijze	2300W Inductive load, cosj = 0.6/230 VAC
Schakelvorm	Steady light
Behuizingsmateriaal	Heat resistant, self-extinguishing thermoplast
Geleverde opties	Without Switch-Off Warning
Kabeldoorsnede	Terminal 4 mm ² Terminal 13 mm ²
Besturing stuurstroom	230 AC V
Verbindingsmodus en capaciteit	3 or 4 conductor operated automatically
Switch Off Warning Type	Flickering
Rated Switching Capacity	16 A 230 V AC
Contactmateriaal	silver-tin-oxide (AgSnO ₂)

Environmental

Omgevingstemperatuur	-25 ... 50 °C
RoHS-status	Following EU Directive 2011/65/EU
Milieu-informatie	2CDU400020D0201

Dimensions

Product netto breedte	17.5 mm
Product netto hoogte	90 mm
Product netto diepte	58 mm
Product netto gewicht	0.07 kg

Container Information

Pakketniveau 1 Units	box 10 stuk
Pakketniveau 1 Breedte	93 mm
Pakketniveau 1 Hoogte	72 mm
Pakketniveau 1 Lengte	183 mm
Pakketniveau 1 Brutogewicht	1.05 kg
Pakketniveau 1 EAN	4016779654166

Ordering

Minimale bestelhoeveelheid	1 stuk
Nummer douanetarief	85364900
E-Number (Finland)	3510147
Land van herkomst	Germany (DE)

Certificates and Declarations (Document Number)

Conformiteitsverklaring - CE	2CDK440040D0201
EAC-certificaat	9AKK108466A2730
Milieu-informatie	2CDU400020D0201
Instructies en handleidingen	2CDE100001P1
RoHS-informatie	2CDK440004K0202
VDE-certificaat	9AKK108466A2521

Popular Downloads

Gegevensblad, technische informatie	9AKK106930A8017
Installatiehandleiding	9AKK108466A2386
Instructies en handleidingen	2CDE100001P1

Classifications

ETIM 7	EC000297 - Staircase lighting timer
ETIM 8	EC000297 - Staircase lighting timer
EPLAN-catalogus boom	Electrical engineering / Sensor, switch, and pushbutton / Switch , pushbutton
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Consumer
CN8	8536 49 00
eClass	V11.0 : 27142307

Categorieën

Laagspanningsproducten en -systemen → Modulaire DIN rail producten → Control and Automation Devices → Staircase Switches

